

TEAC

Hi-Res Inkjet Printer For TEAC Robotic Systems



Color InkJet Disc Printer For TEAC Robotic Systems

- Hi-Res (4800 x 1200dpi) for Hi-Quality Images
- Fast Printing
- Compact Design
- Supports CD/DVD-R
- Large Ink Capacity
- PC or MAC Hosted and Networkable
- Publishing System Ready
- Used with TEAC Robotic Systems Only
Models AL220 (Autoloader) or AP220 (Autopublisher)

TEAC's Color InkJet Disc Printer is the most advanced CD/DVD color printer ever manufactured. Whether you duplicate discs for audio, music, software, video, or data storage, it delivers all the performance you need for high-volume, high-quality disc printing that is extremely affordable. The Color InkJet Disc Printer is your best CD/DVD printing solution!

For the most remarkable print quality, speed and performance, look to the Color InkJet Disc Printer. With incredible 4800 dpi print resolution, (*the best in the world*), all of your discs will have the sharpest text, graphics and photos. Colors are bright, vibrant and truly professional photo-quality, creating a positive, lasting impression.

TEAC's Color InkJet Disc Printer is one of the most intelligent printers on the market today. Not only will it tell you approximately how many discs it will be able to print based on the image you have created, but also knows the differences of the cartridges loaded to maximize your print quality! Now that's smart!

Note: TEAC Inkjet printer is not for stand alone use. It works with TEAC Autoloader and TEAC Autopublisher Systems only.

Specifications

Model:	PIJ
Printing Method:	InkJet
Printing Resolution:	up to 4800 x 1200 dpi
Media:	120mm CD-R or DVD-R, 80mm mini discs and 58mm x 86mm printable surface business card CDs with optional adapter kits (each sold separately) Will also print on ink-jet approved labels after applied to CD surface.
Ink Types:	Dual-cartridge (Uses HP cartridges 56,57,58 and 59)
Colors:	16.7 million with black monochrome
Printing Speed:	Depends upon percentage of coverage, print mode selected, and speed of computer processor
Interface:	Centronics-type parallel
Control Interface:	TTL-level signals for busy printing, tray open/close, etc. Available on rear panel 6-pin mini-DIN connector
Power Voltage:	110v / 220v Auto Switch
Power Consumption:	100W
Dimensions:	6" H x 15"W x 13.5"D 381mm H x 432mm W x 342.9 mm D
Weight:	12lbs. (5.44kg)

Minimum System Requirements:

Pentium-class computer or higher, 64mb RAM, 100MB Free hard drive space, and requires a TEAC Autoloader or Autopublisher Robotic System (shown below).



TEAC robotic systems shown with TEAC P55 Thermal Printer, also sold separately.

Robotic Printer Options



© 2006 TEAC America, Inc. All rights reserved. All trademarks and registered trademarks mentioned herein are the property of their respective companies.

TEAC America, Inc., 7733 Telegraph Road, Montebello, CA 90640 • Phone 323.726.0303 Fax 323.727.7652

www.teac.com/DSPD

DSPD-86760/7-06/5K-UD