

AVoIP compatible



All-in-One Video Distribution

for simultaneous multiple video recording/encoding/streaming/decoding



Digital Signage
in train stations and commercial spaces



Video Streaming
for public viewing in remote locations



Video Distribution
for conferences and presentations



Online Training
for lectures and seminars

4K
UHD 2160p

VS-R265

Full HD
1080p

VS-R265 / VS-R264

H.264
H.265

VS-R265

H.264
Baseline / Main / High

VS-R264

AVoIP
compatible

VS-R265 / VS-R264


PoE+
operation

VS-R265 / VS-R264



Half-rack size AV over IP Compatible Video Streamer/Recorder

The VS-R265 and the VS-264 are AV over IP streaming encoders/decoders that simultaneously record, encode, stream, and decode multiple video streams. The VS-R265 supports 4K using H.265 High Efficiency Video coding (HEVC), a high efficiency coding scheme that delivers H.264 video quality at half the bit rate of H.264, while the VS-R264 supports Full HD video streams using H.264 long GOP encoding with bit rates up to 30 megabits over standard networks suitable for 100Mbps or 1Gbps.



Live Streaming


Both VS-R265 and VS-264 address the growing demand for an external stand-alone encoder for live streaming environments. These models can function as YouTube encoders and also provide live video streaming to popular Content Delivery Networks (CDNs) including Wowza, Ustream, AWS Elemental MediaLive and CloudFront, to name a few.

Professional Audio and Video Streaming for AV over IP Applications

Balanced analog Euroblock/Phoenix low voltage wire connectors and unbalanced analog 1/8" (3.5mm) mini-stereo jacks provide versatile audio I/O connections for a wide range of commercial AV over IP environments, including corporate, education, house of worship, government, industrial and security.

TASCAM Professional Audio Integration with Streaming Video

Audio can be embedded from analog sources and de-embedded to drive networked audio playback for ceiling speakers, or digital audio within the HDMI I/O can be used. An integrated output level configuration function and reference level switching function (up to +20dBu) allows reliable and flexible system structuring when streaming video.



Other features

- Compatible with major streaming protocols like, HLS, RTMP, RTP/RTSP, Multicast and Unicast
- Simultaneous video recording to a SD card/USB flash drive
- Automatic archiving/backup file creation via FTP server
- Including "TASCAM DISCOVERY" app to control multiple units at once
- PoE+ compatible



4K/UHD STREAMER/RECORDER **VS-R265**



FULL HD STREAMER/RECORDER **VS-R264**

Specifications

Video Input/Output	
HDMI IN	Type-A Receptacle x 1
HDMI OUT	Type-A Receptacle x 1
Analog Audio Input	
Balanced	Euroblock (3.81 pitch) x 1
Unbalance	3.5mm Stereo Mini Jack x 1
Analog Audio Output	
Balanced	Euroblock (3.81 pitch) x 1
Unbalance	3.5mm Stereo Mini Jack x 1
Control I/O	
Ethernet / PoE+	RJ-45 x 1
Supported Protocol	TCP/IP, UDP
USB	USB Type-A (USB3.0) x 1
Operating power:	PoE+ Class 4 AC Adapter (TASCAM PS-P1220E, option)
Overall dimensions (WxHxD):	214 x 44.5 x 136.1 mm (including protrusions)
Weight:	850g
Operating temperature:	0 to 40°C / 32 to 104°F

Supported Video Formats

		VS-R265	VS-R265
Input Resolution	2160p	30/29.97/25/24/23.98 fps	-
	1080p	60/59.94/50/30/29.97/25/24/23.98 fps	
	720p	60/59.94/50 fps	
	576p	50 fps	
	480p	60/59.94 fps	
Encoding		H.264 / H.265	H.264 Baseline/Main/High
Bitrate		500k to 30M bps	

Optional Accessories

- PS-P1220E AC Adapter
- AK-RS1 Rack shelf

Related Software

- TASCAM DISCOVERY
Control software for multiple VS-R units via network, supporting Windows and mac OS.
(included in the product, provided on a USB flash drive)

Please note that not all models and colors are available in every country. Design and specifications subject to change without notice. ©2019 TEAC Corporation. All Rights Reserved. All text, images, graphics and other materials on this brochure are subject to the copyright and other intellectual property rights of TEAC Corporation. These materials shall not directly or indirectly be published, reproduced, modified or distributed in any medium. TEAC and TASCAM are trademarks or registered trademarks of TEAC Corporation. Dante is a trademark of Audinate Pty Ltd. Other brands and product names are trademarks or registered trademarks of respective owners.

Authorized Distributors

TASCAM®

TEAC CORPORATION

1-47, Ochiai, Tama-shi, Tokyo 206-8530, Japan
<https://tascam.jp/int>

ISSUED IN JAPAN 2001 D7365